



Distribution Box

Application

Busbar of pin and fork type ensures reliable and efficient terminal connection to MCB, RCCB and other modular electric devices.

Specification and Feature

- Standard segmented connecting pin saves labour tremendously
- High purified copper used to ensure perfect electricity conductivity
- Fire resistant material endures abnormal heating

Technical Data

Busbar 1P+N

- Shape: pin type
- Rated current: 32A
- Rated insulating voltage: 500V AC
- Flammability of plastic part : class 1

Busbar 1P, 2P, 3P, 4P

- Shape: pin type, fork type
- Rated current: 63, 125A
- Rated insulating voltage: 500V AC
- Flammability of plastic part : class 1

End Cap

- Adaptable to full range busbars
- Used to insulate the exposed living parts at both ends of busbar

Terminal Adaptor

- Applicable to busbar for terminal connection
- Fixed on busbar insulating part to secure high reliability
- Connection capacity: 25mm²

Busbar 1P+N

Model	Rated current	Terminals	Length
BP32	32A	56	1m

Busbar pin type 1P, 2P, 3P, 4P

Model	Rated current	Terminals	Length
BP63/1	63A	56(55)	1m
BP63/2	63A	27	1m
BP63/3	63A	18	1m
BP63/4	63A	14	1m
BP125/1	125A	56(55)	1m
BP125/2	125A	27	1m
BP125/3	125A	18	1m
BP125/4	125A	14	1m

Busbar fork type 1P, 2P, 3P, 4P

Model	Rated current	Terminals	Length
BF63/1	63A	56(55)	1m
BF63/2	63A	27	1m
BF63/3	63A	18	1m
BF63/4	63A	14	1m

End Cap

- BC1
- BC2
- BC3
- BC4

Terminal Adaptor

- BA1